

Technical sheet :

1950RT



 **MANITOU**
HANDLING YOUR WORLD

| Capacities | | Imperial |
|--|-----|-----------------------|
| Rated Operating Capacity | | 1951 lb |
| Rated Operating Capacity with Optional Counterweight | | 5858 lb |
| Operating Weight | | 8150 lb |
| Unladen weight | | 7544 lb |
| Operating Capacity At 50% Tipping Load | | 2787 lb |
| Tipping capacity | | 5571 lb |
| Weight and dimensions | | |
| Overall Operating Height - Fully Raised | h27 | 158 in |
| Height to Hinge Pin - Fully Raised | h28 | 120 in |
| Dump reach - Full height | r6 | 26 in |
| Dump angle at full height | a5 | 39 ° |
| Overall Height to top of ROPS | h17 | 78 in |
| Overall length with bucket | l16 | 129 in |
| Departure angle | a2 | 27 ° |
| Ground clearance | m4 | 7 in |
| Overall width less bucket | b1 | 69 in |
| Bucket Width | e1 | 70 in |
| Clearance Radius - Front with Bucket | b18 | 81 in |
| Clearance Circle - Rear | wa1 | 59 in |
| Engine | | |
| Engine brand | | Yanmar |
| Engine model | | 4TNV98C-NMS2V |
| Gross Power | | 51.70 kW |
| Net Power | | 51 kW |
| Max. torque / Engine rotation | | 178 ft/lbs @ 2500 rpm |
| I.C. Engine power rating - Power | | 68.40 Hp / 51 kW |
| Battery voltage | | 12 V |
| Accessory plug | | 120 V |
| Alternator - Ampere | | 100 A |
| Transmission | | |
| Transmission type | | Hydrostatic |
| Hydraulics | | |
| Standard flow - Auxiliary hydraulics | | 19 US gpm |
| Auxiliary Hydraulic Pressure | | 5511 PSI |
| High-Flow Auxiliary Hydraulics - Option | | 30 US gpm |
| High-Flow Auxiliary Hydraulics Pressure - Option | | 6092 PSI |
| Tank capacities | | |
| Hydraulic tank capacity | | 10 US gal |
| Fuel tank | | 16 US gal |
| Liquid cooling tank volume | | 3 US gal |
| Displacement / Number of cylinders | | 0.87 US gal / 4 |
| Noise and vibration | | |
| Noise to environment (LWA) | | 101.40 dB |
| Noise at driving position (LpA) | | 82 dB |
| Whole-Body Vibration (ISO 2631-1) | | 1.10 m/s ² |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes