



Excavator SWE17B



Operating Weight	1.87t (rubber track)
Engine Power	9.9kW/2200rpm
Engine Brand	YANMAR
Standard Bucket Capacity	0.04m ³
Max. Digging Depth	2.15m

Excavator SWE17B

Parameter

ENGINE	
Brand	Yanmar
Model	3TNV70-SSU
Type	3-cylinder water-cooled indirect injection
Displacement	0.854L
Power	9.9kW/2200rpm

DIMENSIONS	
Counterweight Clearance	498mm
Tail Swing Radius	1080mm
Shipping Length	3820mm
Shipping Width	980mm
Shipping Height	2378mm

ELECTRIC SYSTEM	
Nominal Voltage	12V
Batteries	45Ah
Alternator	12V-40A
Starter	12V-1.0kW

WORKING RANGES	
Max. Cutting Height	3509mm
Max. Loading Height	2482mm
Max. Digging Depth	2155mm
Max. Vertical Wall Digging Depth	1551mm
Max. Digging Reach	3850mm
Max. Reach at Ground Level	3472mm
Bucket Digging Force	22.7kN
Stick Digging Force	11.24kN
Ground Pressure	27.8kPa
Swing Speed	10.5rpm

DRIVE	
Max. Travel Speed (2nd/1st)	3.5/2.1km/h
Gradeability	30°
Max. Traction	15.9kN

UNDERCARRIAGE	
Undercarriage Width	980/1310mm
Shoe Width	230mm
Length to Center of Rollers	1170mm
Track Length	1528mm
Track Height	381mm


CAPACITY	
Fuel Tank	23L
Hydraulic Oil Tank	35L

BULLDOZING BOARD	
Independent Moving, Controlled By The Gear Shift Lever	
Length X Width	1310X267mm
Max. Lifting Height	211mm
Max. Cutting Depth	270mm

HYDRAULIC SYSTEM	
Main Pumps	
Type	2 variable displacement pumps, 1 gear pump
Displacement	2x20 + 15 L/min
Working Pressure	20/18 MPa

Excavator SWE 17B

Working Ranges



Load Capacity (standard arm: 0.95m)

B(m) \ A(m)	MAX		3.0m		2.0m	
	Front(kg)	Side(kg)	Front(kg)	Side(kg)	Front(kg)	Side(kg)
2.5	213.00*	209.00*	—	—	—	—
2.0	235.00*	226.00*	244.00	244.00	—	—
1.0	274.00*	210.00	309.00	313.00	500.00*	470.00*
0.0	304.00*	225.00	318.00	283.00	574.00*	435.00
-0.5	330.00*	257.00	326.00	296.00	531.00*	450.00
-1.0	214.50*	200.10*	—	—	238.40*	224.10*

Notes:

- 1) Load with * is limited by hydraulic capacity and based on ISO 10567. Rated loads do not exceed 87% of hydraulic capacity.
- 2) Load without * is limited by tipping load and based on ISO 10567. Rated loads do not exceed 75% of tipping load.

■ SUNWARD INTELLIGENT EQUIPMENT CO.,LTD.

Add: Sunward Intelligent Industrial Park, Xingsha, Changsha, 410100, China.

Tel: (0086-731) 83572 828 Fax: (0086-731) 83572 661

E-mail: international@sunward.com.cn

Web: www.sunward.com.cn

■ SUNWARD EUROPE HEAVY INDUSTRY NV

Add: Nijverheidspark 3, 3580 Beringen, Belgium

Tel: (0032-011) 434666

E-mail: eu@sunward.cc

